

STATE OF UTAH

Department of Environmental Quality

Division of Air Quality

**GENERAL APPROVAL ORDER: Crude Oil and Natural Gas
Well Site and/or Tank Battery**

**Developed By: Utah DAQ
Phone: (801) 536-4000
Website: airquality.utah.gov**

GENERAL APPROVAL ORDER NUMBER

DAQE-ANXXXXXXXXXX-XX

Date: Month XX, 20XX

**Bryce C. Bird
Director**

Abstract

A General Approval Order (GAO) may be issued under the authority of Utah Administrative Code (UAC) R307-401-19. This GAO is for a Crude Oil and/or Natural Gas Well Site and/or Tank Battery. Produced fluids will be brought to the surface from a well. Oil, condensate, water, and gas will be separated from the produced fluid. The oil, condensate, and water will be stored in tanks prior to being transported off site by trucks. The gas may pass through a dehydrator on site. The gas shall either be used as fuel for onsite equipment or be routed to a gas gathering system and sent off site. This GAO will cover a facility that processes up to 50,000 barrels of crude oil and condensate combined per year. A dispersion modeling analysis was conducted for NO₂. Conditions in this GAO reflect the results of this modeling analysis and will ensure protection of the NAAQS.

If a source is not able to construct within the requirements of this GAO, the source must submit a NOI under R307-401-5 and obtain an Approval Order under R307-401-8.

NSPS 40 CFR 60 Subpart A, JJJJ, and OOOO, and MACT 40 CFR 63 Subpart A, HH, and ZZZZ regulations may apply to this source. NESHAP 40 CFR 61 regulations do not apply to this source. Title V of the 1990 Clean Air Act does not apply to this source.

This air quality GAO authorizes the project with the following conditions and failure to comply with any of the conditions may constitute a violation of this order.

SIC code: 1311 (Crude Petroleum & Natural Gas)

Section I: GENERAL PROVISIONS

- I.1 All definitions, terms, abbreviations, and references used in this GAO conform to those used in the UAC R307 and 40 CFR. Unless noted otherwise, references cited in these GAO conditions refer to those rules. [R307-101]
- I.2 The limits set forth in this GAO shall not be exceeded. [R307-401]
- I.3 Modifications to the equipment or processes approved by this GAO that could affect the emissions covered by this GAO must be reviewed and approved. [R307-401-1]
- I.4 All records referenced in this GAO or in other applicable rules, which are required to be kept by the owner/operator, shall be made available to the Director or Director's representative upon request, and the records shall include the two-year period prior to the date of the request. Unless otherwise specified in this GAO or in other applicable state and federal rules, records shall be kept for a minimum of two (2) years. [R307-401-8]
- I.5 At all times, including periods of startup, shutdown, and malfunction, owners and operators shall, to the extent practicable, maintain and operate any equipment approved under this GAO, including associated air pollution control equipment, in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to

the Director which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source. All maintenance performed on equipment authorized by this GAO shall be recorded. [R307-401-4]

- I.6 The owner/operator shall comply with UAC R307-107. General Requirements: Breakdowns. [R307-107]
- I.7 The owner/operator shall comply with UAC R307-150 Series. Inventories, Testing and Monitoring. [R307-150]

Section II: SPECIAL PROVISIONS

II.A The approved installations shall consist of the following equipment (not all the equipment listed is required to be on site):

II.A.1 A Crude Oil and Natural Gas Well Site and/or Tank Battery

II.A.2 Produced Fluids Storage Tanks

Contents: Crude Oil, Condensate, and/or Produced Water
Maximum Site-Wide Capacity: 2,200 barrels
Maximum Individual Capacity: 550 barrels

II.A.3 Dehydrator

Maximum Site-Wide Capacity: 1.0 MMscf/day

II.A.4 VOC Control Device

Minimum Control Efficiency: 98%

II.A.5 Natural Gas-Driven Pneumatic Controllers

II.A.6 Pumpjack, Gas Lift, and Generator Engines

Maximum Site-Wide Rating: 100 hp
Fuel: Natural Gas or LPG

II.A.7 Various Boilers/Heaters

Maximum Site-Wide Capacity: 10.0 MMBtu/hr combined
Fuel: Natural Gas or LPG

II.A.8 Truck Loading Operations

II.A.9 Methanol & Ethylene Glycol Storage Vessels

Maximum Site-Wide Capacity: 500 gallons combined

II.A.10 Heater Treaters

Oil/Water Separator
- listed for informational purposes only -

II.A.11 **Compressors & Pumps**
centrifugal and/or reciprocating
- listed for informational purposes only –

II.A.12 **One (1) Emergency/Overflow Storage Tank**
Maximum Capacity: 550 barrels
- listed for informational purposes only -

II.B Requirements and Limitations

II.B.1 **Site-Wide Requirements**

II.B.1.a The owner/operator shall not exceed 50,000 barrels (1 barrel = 42 gallons) of crude oil and condensate throughput combined per rolling 12-month period. [R307-401-8]

II.B.1.a.1 To determine compliance with a rolling 12-month total, the owner/operator shall calculate a new 12-month total by the twentieth day of each month using data from the previous 12 months. Records of crude oil and condensate throughput shall be kept for all periods when the plant is in operation. Crude oil and condensate throughput shall be determined by process flow meters, load tickets, sales meters, and/or sales records. The records of crude oil and condensate throughput shall be kept on a monthly basis. [R307-401-8]

II.B.1.b All gas produced from the Heater Treater shall either be used as fuel on site or be routed to a gas gathering system and sent off site. [R307-401-8]

II.B.1.c At least once every six months, the owner/operator shall inspect the entire site for VOC leaks using an infrared camera that can detect VOC emissions.

If a VOC leak is detected at any time, the leak shall either be repaired or be evaluated with an analyzer meeting U.S. EPA Method 21, 40 CFR Part 60, Appendix A. If the analyzer's reading is 500 ppm or greater, the leak shall be repaired. Leaks repaired within 15 calendar days of detection will be considered in compliance. [R307-401-8]

II.B.1.c.1 Records of infrared camera inspections and leak detection and repair shall include the following:

- a. the date of the infrared camera inspection,
- b. the name of the person conducting the inspection,
- c. the identification of any component that was determined to be leaking,
- d. the analyzer's reading (if analyzed),
- e. any corrective action taken,
- f. the date corrective action was completed,
- g. the date the component was verified to no longer be leaking.

[R307-401-8]

II.B.1.d Property Boundary Impact Requirement (placeholder). [R307-401-8]

- II.B.1.e A sign shall be located at the site entrance that indicates the presence of oil and gas operations and the potential for exposure to emissions from oil and gas operations. [R307-401-8]
- II.B.1.f Unless otherwise specified in this GAO, visible emissions from any stationary point or fugitive emission source on site shall not exceed 10 percent opacity. [R307-401-8]
- II.B.1.f.1 Unless otherwise specified in this GAO, opacity observations of emissions from stationary sources shall be conducted according to 40 CFR 60, Appendix A, Method 9. [R307-201-3]
- II.B.1.g The owner/operator shall notify the Director in writing when the equipment listed in this GAO has been installed and is operational within 30 days after startup. To ensure proper credit when notifying the Director, send your correspondence to the Director, attn: Compliance Section.

If the owner/operator has not notified the Director in writing on the status of the construction and/or installation within 18 months of a source being granted approval under this GAO, the Director shall require documentation of the continuous construction and/or installation of the operation. If a continuous program of construction and/or installation is not proceeding, the Director may require the source to submit a NOI according to R307-401-5. [R307-401-18]

- II.B.1.h The owner/operator shall submit a list of the actual equipment installed on site and the potential emissions from this equipment to the Director within 180 days after startup. [R307-401-8]
- II.B.1.i The owner/operator shall submit an annual inventory of the actual equipment on site and the actual emissions from the site on or before April 15 of each year following the first full calendar year of operation. [R307-150-1(4)]

II.B.2 **Tank Requirements**

- II.B.2.a VOC emissions from the produced fluids storage tanks shall either be routed to a process unit where the emissions are recycled, incorporated into a product, and/or recovered or be routed to a VOC control device where the emissions are consumed and/or destroyed. [R307-401-8]
- II.B.2.b At least once every month, the thief hatches on the produced fluids storage tanks shall be inspected to ensure the thief hatches are closed and latched and the associated gaskets, if any, are in good working condition. If the gaskets are not in good working condition, they shall be replaced within 15 days of identification of the deficient condition. [R307-401-8]
- II.B.2.b.1 Records of thief hatch inspections shall include the following:
- a. the date of the thief hatch inspection,
 - b. the status of the thief hatches,
 - c. any corrective action taken,
 - d. the date of corrective action.

[R307-401-8]

II.B.3 **Dehydrator Requirements**

II.B.3.a VOC emissions from dehydrators shall either be routed to a process unit where the emissions are recycled, incorporated into a product, and/or recovered or be routed to a VOC control device where the emissions are consumed and/or destroyed. [R307-401-8]

II.B.3 **VOC Control Device Requirements**

II.B.3.a Any VOC control device shall have a minimum control/destruction efficiency of at least 98%. [R307-401-8]

II.B.3.a.1 The owner/operator shall keep and maintain records of the following:

- a. the VOC control device's control/destruction efficiency guaranteed by the manufacturer,
- b. the manufacturer's written operating and maintenance instructions,
- c. the date and type of any maintenance conducted by the owner/operator,

[R307-401-8]

II.B.3.b The VOC control device shall be operated according to the manufacturer's written instructions when gases/vapors are vented to it. [R307-401-8]

II.B.3.c The VOC control device shall operate with no visible emissions. [R307-401-8]

II.B.3.c.1 Visual determination of emissions from the VOC control device shall be conducted according to 40 CFR 60, Appendix A, Method 22. [R307-401-8]

II.B.3.d Stack Height Requirement (placeholder). [R307-401-8]

II.B.4 **Natural Gas-Driven Pneumatic Controller Requirements**

II.B.4.a Each natural gas-driven pneumatic controller shall comply with either a or b:

- a. A natural gas-driven pneumatic controller shall have a bleed rate less than or equal to 6 standard cubic feet per hour and shall comply with 40 CFR 60.5415(d).
- b. The VOC emissions from a natural gas-driven pneumatic controller shall either be routed to a process unit where the emissions are recycled, incorporated into a product, and/or recovered or be routed to a VOC control device where the emissions are consumed and/or destroyed.

[R307-401-8]

II.B.5 **Truck Loading Requirements**

II.B.5.a The owner/operator shall load the tanker trucks on site by the use of submerged loading. [R307-401-8]

II.B.6 **Engine Requirements**

II.B.6.a Any stationary engine on site shall only use natural gas or LPG as fuel. [R307-401-8]

II.B.6.b Any stationary engine on site shall meet the emission standards in 40 CFR 60.4233 for engines manufactured after January 1, 2011. [R307-401-8, 40 CFR 60 Subpart JJJJ]

II.B.6.b.1 The owner/operator shall keep and maintain the following records:

- a. the HC+NO_x emission rate guaranteed by the manufacturer,
- b. the manufacturer's written operating and maintenance instructions,
- c. any maintenance conducted by the owner/operator,
- d. the date of the maintenance activities.

[R307-401-8]

II.B.6.c Stack Height Requirement, (placeholder), and Property Boundary Impact Requirement (placeholder). [R307-401-8]

II.B.7 **Boilers/Heater Requirements**

II.B.7.a All boilers/heaters on site shall only use natural gas or LPG as fuel. [R307-401-8]

II.B.7.b Stack Height Requirement (placeholder). [R307-401-8]

Section III: APPLICABLE FEDERAL REQUIREMENTS

In addition to the requirements of this GAO, all applicable provisions of the following federal programs have been found to apply to this installation. This GAO in no way releases the owner or operator from any liability for compliance with all other applicable federal, state, and local regulations including UAC R307.

NSPS (Part 60), A: General Provisions

NSPS (Part 60), JJJJ: Standards of Performance for Stationary Spark Ignition Internal Combustion Engines

NSPS (Part 60), OOOO: Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution

MACT (Part 63), A: General Provisions

MACT (Part 63), HH: National Emission Standards for Hazardous Air Pollutants From Oil and Natural Gas Production Facilities

MACT (Part 63), ZZZZ: National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

PERMIT HISTORY

This GAO is based on the following documents:

Previous versions of this GAO Version #1 dated Month XX, 20XX

ADMINISTRATIVE CODING

The following information is for UDAQ internal classification use only:

CDS B

NSPS (Part 60), MACT (Part 63),

ACRONYMS

The following lists commonly used acronyms and associated translations as they apply to this document:

40 CFR	Title 40 of the Code of Federal Regulations
AO	Approval Order
BACT	Best Available Control Technology
CAA	Clean Air Act
CAAA	Clean Air Act Amendments
CDS	Classification Data System (used by EPA to classify sources by size/type)
CEM	Continuous emissions monitor
CEMS	Continuous emissions monitoring system
CFR	Code of Federal Regulations
CMS	Continuous monitoring system
CO	Carbon monoxide
CO ₂	Carbon Dioxide
CO _{2e}	Carbon Dioxide Equivalent - 40 CFR Part 98, Subpart A, Table A-1
COM	Continuous opacity monitor
DAQ	Division of Air Quality (typically interchangeable with UDAQ)
DAQE	This is a document tracking code for internal UDAQ use
EPA	Environmental Protection Agency
FDCP	Fugitive dust control plan
GHG	Greenhouse Gas(es) - 40 CFR 52.21 (b)(49)(i)
GWP	Global Warming Potential - 40 CFR Part 86.1818-12(a)
HAP or HAPs	Hazardous air pollutant(s)
ITA	Intent to Approve
LB/HR	Pounds per hour
MACT	Maximum Achievable Control Technology
MMBTU	Million British Thermal Units
NAA	Nonattainment Area
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standards for Hazardous Air Pollutants
NOI	Notice of Intent
NO _x	Oxides of nitrogen
NSPS	New Source Performance Standard
NSR	New Source Review
PM ₁₀	Particulate matter less than 10 microns in size
PM _{2.5}	Particulate matter less than 2.5 microns in size
PSD	Prevention of Significant Deterioration
PTE	Potential to Emit
R307	Rules Series 307
R307-401	Rules Series 307 - Section 401
SO ₂	Sulfur dioxide
Title IV	Title IV of the Clean Air Act
Title V	Title V of the Clean Air Act
TPY	Tons per year
UAC	Utah Administrative Code
UDAQ	Utah Division of Air Quality (typically interchangeable with DAQ)
VOC	Volatile organic compounds